



Mechanical SHORTSLEEVE™ Fittings are designed for use on 4 (DN 100) (DN 300) cast iron pipe. They may be used with SHORTSTOPP® Plugging Equipment to repair or replace a damaged section of cast iron main. Mechanical SHORTSLEEVE™ Fittings can also be used without the machine

max

M fittings



**4- to 12-inch ( 100 - 300)**

™

Complete with Blind Flange, Studs, Nuts,  
Gasket and Completion Plug

Size		Weight		Pipe OD +/- 0.060" (1.5 mm)		Part Number
Inches	DN	Lbs.	Kg.	Inches	mm	
4	100	88	40	4.80	122	06-6586-0000
6	150	148	67	6.90	175	06-6587-0000
8	200	212	96	9.05	230	06-6588-0000
10	250	290	132	11.10	282	06-6589-0000
12	300	413	187	13.20	335	06-6590-0000

**4- to 12-inch ( 100 - 300)**

Excludes Blind Flange, Studs, Nuts, Gasket  
and Completion Plug

Size		Weight		Pipe OD +/- 0.060" (1.5 mm)		Part Number
Inches	DN	Lbs.	Kg.	Inches	mm	
4	100	63	28	4.80	122	06-7263-0000
6	150	116	53	6.90	175	06-7280-0000
8	200	127	58	9.05	230	06-7330-0000
10	250	176	80	11.10	282	06-7331-0000
12	300	280	127	13.20	335	06-7332-0000

Note: Mechanical Tapping Fittings are designed for use on cast iron pipe only.

Size		A		B		Min. Thru-bore	
Inches	DN	Inches	mm	Inches	mm	Inches	mm
4	100	9-1/2	241	11-3/8	289	3-29/32	99
6	150	11-7/8	301	13-3/8	340	5-29/32	150
8	200	14-7/16	367	16-3/4	425	7-13/16	198
10	250						



The 8" x 6" (DN 200 x DN 150) and the  
12" x 10" (DN 300 x DN 250) are used to  
adapt valve to next smaller size Mechanical  
SHORTSLEEVE™.

